

6.3 Type code MAD130

Type short description	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3
------------------------	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

Fig. 6-4: Type code MAD130 (1/2)

Type codes IndraDyn A

Type short description	1	2	3	4	5	6	7	8	9	1	2	3	4	5	6	7	8	9	2	0	1	2	3	4	5	6	7	8	9	3	0	1	2	3	4	5	6	7	8	9	0	4				
Example:	M	A	D	1	3	0	B	-	0	1	5	0	-	S	A	-	S	2	-	A	G	0	-	0	5	-	N	1																		
09 Holding brake																																														
Without holding brake.....																																														
Electrically-released, 80 Nm.....																																														
Electrically-clamped, 100 Nm.....																																														
10 Mounting style																																														
Flange mounting.....																																														
Flange and foot mounting.....																																														
11 Bearing ⁴⁾																																														
Fixed bearing A-Side.....																																														
High speed																																														
Standard																																														
Reinforced bearing																																														
12 Vibration severity																																														
A, according to DIN EN 60034-14																																														
B, according to DIN EN 60034-14																																														
C, spezifikation according to IndraDyn A - documentation																																														

Note:

- 1) Ex type for cluster II 2G Ex pd IIB T3 according to DIN EN 60079 ff Encoder "M6" or "S6" are only available with Cooling mode "SL", not with Electrical connection "A", "B", "R" and "L" and only with Shaft "G", "P" or "K" and Bearing "A", "N" or "V"
- 2) According to DIN IEC 60204-1 and DIN IEC 60364-5-52
- 3) Shaft "F", "M" and "R" are only available with shaft sealing ring
- 4) Bearing "A" is only available with Holding brake "0" and Vibration severity "1"
Bearing "H" is not available with Encoder "S6" or "M6" and only with Shaft "H" and Holding brake "0"
- 5) Vibration severity "4" is only availbale with Length "B" or "C" and Bearing "N" or "H"

DCCS-40001-130_TCO_N_EN_2015-12-03_2v2

Fig. 6-5: Type code MAD130 (2/2)