

6.2 MKE037

Short text column	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0
Example:	M	K	E	0	3	7	B	-	1	4	-	A	G	0	-	B	E	N	N																					

Product

MKE = MKE

Size

037 = 037

Length

Length = B

Winding

MKE037B = 144

Encoder

Optical encoder, Singleturn Hiperface with 128 inkrements S1 = A

Optical encoder, Multiturn absolute Hiperface with 128 inkrements (M1) = C

Shaft

Plain shaft (with shaft sealing ring). = G

Shaft with key per DIN 6885-1 (with shaft sealing ring) = P

Holding brake

Without holding brake. = 0

Holding brake Nm = 1

Electrical connection 1)

Terminal box, A-side = A

Terminal box, B-side = B

Terminal box, left = L

Terminal box, right = R

Housing design 2)


Per ATEX standard = E

Per GOST-R-standard = G

Per UL-standard = U

Other design

None = NN



Picture 1

- Remark:
- 1) = Looking from front onto dirven shaft (see picture 1)
- 2) = Housing designs "E" or "G" are only available with electrical connection "B"

Fig.6-4: Type code MKE037