

6.8 Size MSK071

Abbrev. Column		1										2										3										4									
		1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0
Example:		M	S	K	0	7	1	D	-	0	3	0	0	-	N	N	-	S	1	-	U	G	0	-	N	N	N	N													
1.	Product																																								
1.1	MSK = MSK																																								
2.	Size																																								
2.1	071 = 071																																								
3.	Length																																								
3.1	Lengths = C, D, E																																								
4.	Winding code																																								
4.1	MSK071C = 0200, 0300, 0450																																								
4.2	MSK071D = 0200, 0300, 0450																																								
4.3	MSK071E = 0200, 0300, 0450																																								
5.	Cooling mode																																								
5.1	liquid cooling = FN ①																																								
5.2	natural convection = NN																																								
6.	Encoder																																								
6.1	optical encoder, singleturn Hiperface, with 128 increments. = S1																																								
6.2	optical encoder, singleturn EnDat2.1, with 2048 increments. = S2																																								
6.3	optical encoder, multiturn-absolute Hiperface, with 128 increments. = M1																																								
6.4	optical encoder, multiturn-absolute EnDat2.1, with 2048 increments. = M2																																								
7.	Electrical connection																																								
7.1	Plug, rotatable 240° = U																																								
8.	Shaft																																								
8.1	plain shaft with shaft sealing ring (standard) = G																																								
8.2	shaft with keyway per DIN 6885-1 with shaft sealing ring . . . = P																																								
9.	Holding brake																																								
9.1	without holding brake. = 0																																								
9.2	holding brake, electrically-released, 23 Nm. = 1																																								
9.3	holding brake, electrically-released, 30 Nm. = 2																																								

Fig.6-29: Type Codes MSK071 (page 1)

[illegible]

Fig.6-30: Type Codes MSK071 (page 2)